

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

Graffiti Shield Remover

Product no.

-

REACH registration number

Not applicable

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Cleaning liquid

Uses advised against

-

The full text of any mentioned and identified use categories are given in section 16

1.3. Details of the supplier of the safety data sheet

Company and address

Blue & Green AB
Stenorsvägen 52
261 44 Landskrona
Sweden
Tfn: +46 418 399000
Fax: +46 418 13199
www.blueandgreen.se

E-mail

info@blueandgreen.se

SDS date

2020-11-16

SDS Version

1.0

1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service). See section 4 "First aid measures".

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Skin Corr. 1B; H314

Eye Dam. 1; H318

See full text of H-phrases in section 2.2.

2.2. Label elements

Hazard pictogram(s)**Signal word**

Danger

Hazard statement(s)

Causes severe skin burns and eye damage. (H314)

Precautionary statements

General

If medical advice is needed, have product container or label at hand. (P101).

According to EC-Regulation 2015/830

**Prevention
Response**

Keep out of reach of children. (P102).
Do not breathe mist/vapours/fume/spray. (P260).
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. (P303+P361+P353).

**Storage
Disposal**

Store locked up. (P405).
Dispose of contents/container to an approved waste disposal plant. (P501).

Identity of the substances primarily responsible for the major health hazards

2-aminoethanol

Additional labelling

Not applicable

Unique formula identifier (UFI)

FMP7-WVKV-3007-H0J6

2.3. Other hazards

Not applicable

Additional warnings

Tactile warning. If this product is sold in retail, it must be delivered with child-resistant fastening.

VOC (volatile organic compound)

Not applicable

SECTION 3: Composition/information on ingredients

3.1/3.2. Substances/Mixtures

NAME: 2-aminoethanol
IDENTIFICATION NOS.: CAS-no: 141-43-5 EC-no: 205-483-3 REACH-no: 01-2119486455-28 Index-no: 603-030-00-8
CONTENT: 10 - <15%
CLP CLASSIFICATION: Acute Tox. 4, STOT SE 3, Skin Corr. 1B
H302, H312, H314, H332, H335
NOTE: O L

NAME: 2-butoxyethanol
IDENTIFICATION NOS.: CAS-no: 111-76-2 EC-no: 203-905-0 REACH-no: 01-2119475108-36 Index-no: 603-014-00-0
CONTENT: 5 - <10%
CLP CLASSIFICATION: Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2
H302, H312, H315, H319, H332
NOTE: O L

NAME: 2-(2-butoxyethoxy)ethanol
IDENTIFICATION NOS.: CAS-no: 112-34-5 EC-no: 203-961-6 REACH-no: 01-2119475104-44 Index-no: 603-096-00-8
CONTENT: 5 - <10%
CLP CLASSIFICATION: Eye Irrit. 2
H319
NOTE: L

(*) O = Organic solvent L = European occupational exposure limit. See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

ATEmix(inhale, vapour) > 20
ATEmix(dermal) > 2000
ATEmix(oral) > 2000
Eye Cat. 1 Sum = Sum(Ci/S(G)CLi) = 2.6664 - 3.9996
Skin Cat. 2 Sum = Sum(Ci/S(G)CLi) = 8.4 - 12.6

Detergent:

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. The doctor can contact The National Poisons Information Service: Dial 0344 892 0111 (24 h service). Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Bring the person into fresh air and stay with him/her.

According to EC-Regulation 2015/830

Skin contact

Immediately remove contaminated clothing and shoes. Ensure that skin, which has been exposed to the material, is washed thoroughly with soap and water.

Eye contact

Remove contact lenses. Flush eyes with plenty of water or salt water (20-30°C) for at least 15 minutes and continue until irritation stops. Make sure you flush under the upper and lower eyelids. Seek medical assistance immediately and continue flushing.

Ingestion

In the case of ingestion, contact a doctor immediately and bring the safety data sheet or label. If the person is conscious, give them water. DO NOT try to induce vomiting, unless this is recommended by a doctor. Hold head facing down to prevent vomit returning to the mouth and throat. Prevent shock by keeping the injured person warm and calm. Initiate immediate resuscitation if breathing stops. If unconscious, roll the injured person into recovery position. Call an ambulance.

Burns

Not applicable

4.2. Most important symptoms and effects, both acute and delayed

Tissue-damaging effects: This product contains substances with skin corrosive properties. Inhaled vapour or aerosols may produce adverse effects to lungs, -irritations and burns in the respiratory organs -as well as coughing. Dermal contact and contact with the eye cause irreversible effects.

This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs.

Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned: Get immediate medical advice/attention.

Information to medics

Bring this safety data sheet.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Recommended: alcohol-resistant foam, carbonic acid, powder, water mist.

5.2. Special hazards arising from the substance or mixture

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous catabolic substances are produced. These are: Nitrogen oxides. Carbon oxides. Fire will result in dense black smoke. Exposure to combustion products may harm your health. Fire fighters should wear appropriate protection equipment.

Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid direct contact with spilled substances.

6.2. Environmental precautions

No specific requirements.

6.3. Methods and material for containment and cleaning up

Use sand, sawdust, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations.

6.4. Reference to other sections

See section on "Disposal considerations" in regard of handling of waste. See section on 'Exposure controls/personal protection' for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Smoking, storage of tobacco, consumption and storage of food or liquids are not allowed in the workrooms. See section on 'Exposure controls/personal protection' for information on personal protection. Avoid direct contact with the product.

7.2. Conditions for safe storage, including any incompatibilities

Always store in containers of the same material as the original container. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

According to EC-Regulation 2015/830

Storage temperature

No data available.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

OEL

2-(2-butoxyethoxy)ethanol

Long-term exposure limit (8-hour TWA reference period): 10 ppm | 67,5 mg/m³

Short-term exposure limit (15-minute reference period): 15 ppm | 101.2 mg/m³

2-butoxyethanol

Long-term exposure limit (8-hour TWA reference period): 25 ppm | 123 mg/m³

Short-term exposure limit (15-minute reference period): 50 ppm | - mg/m³

Comments: Sk;BMGV (Bmgv = Biological Monitoring Guidance Value. Sk = Can be absorbed through skin.)

2-aminoethanol

Long-term exposure limit (8-hour TWA reference period): 1 ppm | 2,5 mg/m³

Short-term exposure limit (15-minute reference period): 3 ppm | 7.6 mg/m³

Comments: Sk (Sk = Can be absorbed through skin.)

DNEL / PNEC

DNEL (2-butoxyethanol): 3.2 mg/kg bw/day

Exposure: Oral

Duration of Exposure: Long term – Systemic effects - General population

DNEL (2-butoxyethanol): 49 mg/m³

Exposure: Inhalation

Duration of Exposure: Long term – Systemic effects - General population

DNEL (2-butoxyethanol): 38 mg/kg bw/day

Exposure: Dermal

Duration of Exposure: Long term – Systemic effects - General population

DNEL (2-butoxyethanol): 426 mg/m³

Exposure: Inhalation

Duration of Exposure: Short term – Systemic effects - General population

DNEL (2-butoxyethanol): 123 mg/m³

Exposure: Inhalation

Duration of Exposure: Short term – Local effects - General population

DNEL (2-butoxyethanol): 98 mg/m³, 20 ppm

Exposure: Inhalation

Duration of Exposure: Long term – Systemic effects - Workers

DNEL (2-butoxyethanol): 246 mg/m³, 50 ppm

Exposure: Inhalation

Duration of Exposure: Short term – Local effects - Workers

DNEL (2-butoxyethanol): 663 mg/m³, 135 ppm

Exposure: Inhalation

Duration of Exposure: Short term – Systemic effects - Workers

DNEL (2-butoxyethanol): 89 mg/kg bw/day

Exposure: Dermal

Duration of Exposure: Short term – Systemic effects - Workers

DNEL (2-butoxyethanol): 13.4 mg/kg bw/day

Exposure: Oral

Duration of Exposure: Short term – Systemic effects - General population

DNEL (2-butoxyethanol): 44.5 mg/kg bw/day

Exposure: Dermal

Duration of Exposure: Short term – Systemic effects - General population

DNEL (2-(2-butoxyethoxy)ethanol): 83 mg/kg

Exposure: Dermal

Duration of Exposure: Long term – Systemic effects - Workers

DNEL (2-(2-butoxyethoxy)ethanol): 67.5 mg/m³

According to EC-Regulation 2015/830

Exposure: Inhalation
Duration of Exposure: Long term – Systemic effects - Workers

DNEL (2-(2-butoxyethoxy)ethanol): 67.5 mg/m³
Exposure: Inhalation
Duration of Exposure: Long term – Local effects - Workers

DNEL (2-(2-butoxyethoxy)ethanol): 5 mg/kg bw/d
Exposure: Oral
Duration of Exposure: Long term – Systemic effects - General population

DNEL (2-(2-butoxyethoxy)ethanol): 50 mg/kg bw/d
Exposure: Dermal
Duration of Exposure: Long term – Systemic effects - General population

DNEL (2-(2-butoxyethoxy)ethanol): 40.5 mg/m³
Exposure: Inhalation
Duration of Exposure: Long term – Local effects - General population

DNEL (2-(2-butoxyethoxy)ethanol): 101.2 mg/m³
Exposure: Inhalation
Duration of Exposure: Short term – Local effects - Workers

DNEL (2-(2-butoxyethoxy)ethanol): 40.5 mg/m³
Exposure: Inhalation
Duration of Exposure: Long term – Systemic effects - General population

DNEL (2-(2-butoxyethoxy)ethanol): 60.7 mg/m³
Exposure: Inhalation
Duration of Exposure: Short term – Local effects - General population

DNEL (2-aminoethanol): 1 mg/kg bw/d
Exposure: Dermal
Duration of Exposure: Long term – Systemic effects - Workers

DNEL (2-aminoethanol): 3.3 mg/m³
Exposure: Inhalation
Duration of Exposure: Long term – Systemic effects - Workers

DNEL (2-aminoethanol): 3.3 mg/m³
Exposure: Inhalation
Duration of Exposure: Long term – Local effects - Workers

DNEL (2-aminoethanol): 0.24 mg/kg bw/d
Exposure: Dermal
Duration of Exposure: Long term – Systemic effects - General population

DNEL (2-aminoethanol): 2 mg/m³
Exposure: Inhalation
Duration of Exposure: Long term – Systemic effects - General population

DNEL (2-aminoethanol): 2 mg/m³
Exposure: Inhalation
Duration of Exposure: Long term – Local effects - General population

DNEL (2-aminoethanol): 3.75 mg/kg bw/d
Exposure: Oral
Duration of Exposure: Long term – Systemic effects - General population

PNEC (2-butoxyethanol): 8.8 mg/l
Exposure: Freshwater

PNEC (2-butoxyethanol): 0.88 mg/l
Exposure: Marine water

PNEC (2-butoxyethanol): 463 mg/l
Exposure: Sewage Treatment Plant

PNEC (2-butoxyethanol): 34.6 mg/kg dw
Exposure: Freshwater sediment

PNEC (2-butoxyethanol): 3.46 mg/kg dw
Exposure: Marine water sediment

According to EC-Regulation 2015/830

PNEC (2-butoxyethanol): 2.8 mg/kg dw
Exposure: Soil

PNEC (2-butoxyethanol): 9.1 mg/l
Exposure: Intermittent release

PNEC (2-(2-butoxyethoxy)ethanol): 200 mg/l
Exposure: Sewage Treatment Plant

PNEC (2-(2-butoxyethoxy)ethanol): 0.44 mg/kg dw
Exposure: Marine water sediment

PNEC (2-(2-butoxyethoxy)ethanol): 4.4 mg/kg dw
Exposure: Freshwater sediment

PNEC (2-(2-butoxyethoxy)ethanol): 1 mg/l
Exposure: Freshwater

PNEC (2-(2-butoxyethoxy)ethanol): 0.1 mg/l
Exposure: Marine water

PNEC (2-(2-butoxyethoxy)ethanol): 3.9 mg/l
Exposure: Intermittent release

PNEC (2-(2-butoxyethoxy)ethanol): 0.32 mg/kg dw
Exposure: Soil

PNEC (2-aminoethanol): 0.085 mg/l
Exposure: Freshwater

PNEC (2-aminoethanol): 0.0085 mg/l
Exposure: Marine water

PNEC (2-aminoethanol): 0.434 mg/kg dw
Exposure: Freshwater sediment

PNEC (2-aminoethanol): 0.0434 mg/kg dw
Exposure: Marine water sediment

PNEC (2-aminoethanol): 1.29 mg/kg dw
Exposure: Soil

PNEC (2-aminoethanol): 100 mg/l
Exposure: Sewage Treatment Plant

PNEC (2-aminoethanol): 0.028 mg/l
Exposure: Intermittent release

8.2. Exposure controls

Compliance with the accepted occupational exposure limits values should be controlled on a regular basis.

General recommendations

Observe general occupational hygiene standards.

Exposure scenarios

There is no appendix to this safety data sheet.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

Ensure emergency eyewash and -showers are clearly marked.

Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

Measures to avoid environmental exposure

Keep containment materials near the workplace. If possible, collect spillage during work.

Individual protection measures, such as personal protective equipment

According to EC-Regulation 2015/830



Generally

Use only CE marked protective equipment.

Respiratory Equipment

Recommended: A. Class 3 (High capacity). Brown

Skin protection

Dedicated work clothing should be worn. Wear a protective suit in the event of prolonged periods of work with the product.

Hand protection

Nitrile rubber

Breakthrough time: > 480 minutes (Class 6)

Eye protection

Wear safety glasses with side shields.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|------------------------------|--------------------|
| Form | Liquid |
| Colour | Yellowish |
| Odour | Characteristic |
| Odour threshold (ppm) | No data available. |
| pH | No data available. |
| Viscosity (40°C) | No data available. |
| Density (g/cm ³) | No data available. |

Phase changes

| | |
|---|--------------------|
| Melting point (°C) | No data available. |
| Boiling point (°C) | No data available. |
| Vapour pressure | No data available. |
| Decomposition temperature (°C) | No data available. |
| Evaporation rate (n-butylacetate = 100) | No data available. |

Data on fire and explosion hazards

| | |
|--------------------------|--------------------|
| Flash point (°C) | No data available. |
| Ignition (°C) | No data available. |
| Auto flammability (°C) | No data available. |
| Explosion limits (% v/v) | No data available. |
| Explosive properties | No data available. |

Solubility

| | |
|-----------------------------|--------------------|
| Solubility in water | Soluble |
| n-octanol/water coefficient | No data available. |

9.2. Other information

| | |
|-------------------------|--------------------|
| Solubility in fat (g/L) | No data available. |
|-------------------------|--------------------|

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available

10.2. Chemical stability

The product is stable under the conditions, noted in the section "Handling and storage".

10.3. Possibility of hazardous reactions

Nothing special

10.4. Conditions to avoid

Nothing special

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

According to EC-Regulation 2015/830

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Substance: 2-(2-butoxyethoxy)ethanol
 Species: Rabbit
 Test: LD50
 Route of exposure: Dermal
 Result: 2764 mg/kg

Substance: 2-(2-butoxyethoxy)ethanol
 Species: Mouse
 Test: LD50
 Route of exposure: Oral
 Result: 2410 mg/kg

Substance: 2-(2-butoxyethoxy)ethanol
 Species: Rat
 Test: LD50
 Route of exposure: Oral
 Result: >2000 mg/kg

Substance: 2-(2-butoxyethoxy)ethanol
 Species: Rat
 Test: LC50
 Route of exposure: Inhalation
 Result: >29 ppm 2h

Substance: 2-butoxyethanol
 Species: Guinea pig
 Test: LD0
 Route of exposure: Dermal
 Result: >2000 mg/kg

Substance: 2-butoxyethanol
 Species: Rat
 Test: LD50
 Route of exposure: Oral
 Result: 1300 mg/kg

Substance: 2-butoxyethanol
 Species: Guinea pig
 Test: LD50
 Route of exposure: Oral
 Result: 1414 mg/kg

Substance: 2-butoxyethanol
 Species: Rat
 Test: LC50
 Route of exposure: Inhalation
 Result: 2.56 mg/l/4h

Substance: 2-aminoethanol
 Species: Rat
 Test: LD50
 Route of exposure: Dermal
 Result: 2504 mg/kg

Substance: 2-aminoethanol
 Species: Rat
 Test: LD50
 Route of exposure: Oral
 Result: 1089 mg/kg

Substance: 2-aminoethanol
 Species: Rat
 Test: LD50
 Route of exposure: Inhalation
 Result: 1478 mg/m3

Skin corrosion/irritation

Causes severe skin burns and eye damage.

According to EC-Regulation 2015/830

Data on substance: 2-(2-butoxyethoxy)ethanol

Test: OECD Guideline 404

Organism: Rabbit

Result: not irritating

Serious eye damage/irritation

Causes serious eye damage.

Data on substance: 2-(2-butoxyethoxy)ethanol

Test: OECD Guideline 404

Organism: Rabbit

Result: irritating

Respiratory or skin sensitisation

Data on substance: 2-(2-butoxyethoxy)ethanol

Test: OECD Guideline 406

Organism: Guinea pig

Result: Negative

Data on substance: 2-aminoethanol

Germ cell mutagenicity

No data available.

Carcinogenicity

No data available.

Reproductive toxicity

No data available.

STOT-single exposure

No data available.

STOT-repeated exposure

No data available.

Aspiration hazard

No data available.

Long term effects

Tissue-damaging effects: This product contains substances with skin corrosive properties. Inhaled vapour or aerosols may produce adverse effects to lungs, -irritations and burns in the respiratory organs -as well as coughing. Dermal contact and contact with the eye cause irreversible effects.

This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

SECTION 12: Ecological information

12.1. Toxicity

Substance: 2-(2-butoxyethoxy)ethanol

Species: Daphnia

Test: EC50

Duration: 48h

Result: >100 mg/l

Substance: 2-(2-butoxyethoxy)ethanol

Species: Fish

Test: LC50

Duration: 96h

Result: >100 mg/l

Substance: 2-(2-butoxyethoxy)ethanol

Species: Algae

Test: EC50

Duration: 96h

Result: >100 mg/l

Substance: 2-butoxyethanol

Species: Daphnia

Test: NOEC

Duration: 21d

Result: 100 mg/l

Substance: 2-butoxyethanol

Species: Daphnia

Test: EC50

Duration: 48h

Result: 1550 mg/l

Substance: 2-butoxyethanol

Species: Fish

Test: NOEC

According to EC-Regulation 2015/830

Duration: 21d
Result: 100 mg/l

Substance: 2-butoxyethanol
Species: Fish
Test: LC50
Duration: 96h
Result: 1474 mg/l

Substance: 2-butoxyethanol
Species: Algae
Test: EC50
Duration: 72h
Result: 1840 mg/l

Substance: 2-aminoethanol
Species: Daphnia
Test: NOEC
Duration: 21d
Result: 0.85 mg/l

Substance: 2-aminoethanol
Species: Daphnia
Test: EC50
Duration: 48h
Result: 65 mg/l

Substance: 2-aminoethanol
Species: Fish
Test: LC50
Duration: 96h
Result: 349 mg/l

Substance: 2-aminoethanol
Species: Algae
Test: EC50
Duration: 72h
Result: 2.5 mg/l

12.2. Persistence and degradability

| Substance | Biodegradability | Test | Result |
|---------------------------|------------------|------------------------------|--------|
| 2-(2-butoxyethoxy)ethanol | Yes | Modified OECD Screening Test | 100% |
| 2-butoxyethanol | Yes | CO2 Evolution Test | 90,4 |
| 2-aminoethanol | Yes | DOC Die-Away Test | >90% |

12.3. Bioaccumulative potential

| Substance | Potential bioaccumulation | LogPow | BCF |
|---------------------------|---------------------------|--------|-------------------|
| 2-(2-butoxyethoxy)ethanol | No | 1 | No data available |
| 2-butoxyethanol | No | 0.81 | No data available |
| 2-aminoethanol | No | -1.91 | No data available |

12.4. Mobility in soil

2-(2-butoxyethoxy)ethanol: Log Koc= 0.8703, Calculated from LogPow (High mobility potential.).
2-butoxyethanol: Log Koc= 0.719839, Calculated from LogPow (High mobility potential.).
2-aminoethanol: Log Koc= -1.434129, Calculated from LogPow (High mobility potential.).

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

12.6. Other adverse effects

Nothing special

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product is covered by the regulations on hazardous waste.

Waste

EWC code

-

Specific labelling

Not applicable

Contaminated packing

According to EC-Regulation 2015/830

Contaminated packaging must be disposed of similarly to the product.

SECTION 14: Transport information

14.1 – 14.4

This product is within scope of the regulations of transport of dangerous goods.

ADR/RID

| | |
|----------------------------------|---------------------------------------|
| 14.1. UN number | 2491 |
| 14.2. UN proper shipping name | ETHANOLAMINE or ETHANOLAMINE SOLUTION |
| 14.3. Transport hazard class(es) | 8 |
| 14.4. Packing group | III |
| Notes | - |
| Tunnel restriction code | E |

IMDG

| | |
|-----------------------|---------------------------------------|
| UN-no. | 2491 |
| Proper Shipping Name | ETHANOLAMINE or ETHANOLAMINE SOLUTION |
| Class | 8 |
| PG* | III |
| EmS | F-A, S-B |
| MP** | No |
| Hazardous constituent | - |

IATA/ICAO

| | |
|----------------------|---------------------------------------|
| UN-no. | 2491 |
| Proper Shipping Name | ETHANOLAMINE or ETHANOLAMINE SOLUTION |
| Class | 8 |
| PG* | III |

14.5. Environmental hazards

-

14.6. Special precautions for user

-

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available

(*) Packing group

(**) Marine pollutant

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

People under the age of 18 shall not be exposed to this product cf. Council Directive 94/33/EC of 22 June 1994 on the protection of young people at work.

Demands for specific education

-

Additional information

Not applicable

Seveso

-

Biocidal reg. no.

Not applicable

Sources

Council Directive 92/85/EEC on the introduction of measures to encourage improvements in the safety and health at work of pregnant workers and workers who have recently given birth or are breastfeeding.

Council Directive 94/33/EC of 22 June 1994 on the protection of young people at work.

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677. The Stationery Office, 2002.

Regulation (EC) No 648/2004 of the European Parliament and of the Council of 31 March 2004 on detergents.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (CLP).

Regulation (EC) 1907/2006 (REACH).

15.2. Chemical safety assessment

According to EC-Regulation 2015/830

No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

H302 - Harmful if swallowed.
H312 - Harmful in contact with skin.
H314 - Causes severe skin burns and eye damage.
H315 - Causes skin irritation.
H319 - Causes serious eye irritation.
H332 - Harmful if inhaled.
H335 - May cause respiratory irritation.

The full text of identified uses as mentioned in section 1

-

Additional label elements

Not applicable

Other

In accordance with Regulation (EC) No. 1272/2008 (CLP) the evaluation of the classification of the mixture is based on:

The classification of the mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP)

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The safety data sheet is validated by

David Löwenstein

Date of last essential change (First cipher in SDS version)

-

Date of last minor change (Last cipher in SDS version)

-