# SAFETY DATA SHEET

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

#### **Trade name**

Graffiti Shield Winter

Product no.

# **REACH registration number**

Not applicable

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

### Relevant identified uses of the substance or mixture

Graffiti protection

**Uses advised against** 

The full text of any mentioned and identified use categories are given in section 16

### 1.3. Details of the supplier of the safety data sheet

### **Company and address**

Blue & Green AB Stenorsvägen 52

261 44 Landskrona

Sweden

Tfn: +46 418 399000 Fax: +46 418 13199 www.blueandgreen.se

#### E-mail

info@blueandgreen.se

#### SDS date

2020-08-10

#### **SDS Version**

1.0

# 1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service). See section 4 "First aid measures".

### **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

Eve Irrit. 2: H319

See full text of H-phrases in section 2.2.

#### 2.2. Label elements

### **Hazard pictogram(s)**



### Signal word

Warning

#### **Hazard statement(s)**

Causes serious eye irritation. (H319)

# **Precautionary statements**

General

If medical advice is needed, have product container or label at hand. (P101). Keep out of reach of children. (P102).



Prevention Wash hands/exposed skin thoroughly after handling. (P264).

Wear eye protection/gloves. (P280).

Response If eye irritation persists: Get medical advice/attention. (P337+P313).

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing. (P305+P351+P338).

Storage - Disposal -

#### Identity of the substances primarily responsible for the major health hazards

Not applicable

#### Additional labelling

Contains 1,2-benzisothiazol-3(2H)-one 1,2-benzisothiazolin-3-one. May produce an allergic reaction. (EUH208).

# Unique formula identifier (UFI)

#### 2.3. Other hazards

This product contains an organic solvent. Repeated or prolonged exposure to organic solvents may result in adverse effects to the nervous system and internal organs such as liver and kidneys.

#### Additional warnings

Not applicable

### **VOC (volatile organic compound)**

Not applicable

# **SECTION 3: Composition/information on ingredients**

#### 3.1/3.2. Substances/Mixtures

NAME: propan-2-ol

IDENTIFICATION NOS.: CAS-no: 67-63-0 EC-no: 200-661-7 REACH-no: 01-2119457558-25 Index-no: 603-117-00-0

CONTENT: 10 - <15%

CLP CLASSIFICATION: Flam. Liq. 2, STOT SE 3, Eye Irrit. 2

H225, H319, H336

NOTE: O

NAME: Alcohols (C16-18) ethoxylated

IDENTIFICATION NOS.: CAS-no: 68439-49-6 REACH-no: Polymer

CONTENT: 1 - <2.5%

CLP CLASSIFICATION: Aquatic Acute 1, Acute Tox. 4, Eye Irrit. 2, H400,H302,H319

(\*) O = Organic solvent See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

#### Other information

ATEmix(inhale, vapour) > 20 ATEmix(inhale, dust/mist) > 5 ATEmix(inhale, gas) > 20000 ATEmix(dermal) > 2000 ATEmix(oral) > 2000

Eye Cat. 2 Sum = Sum(Ci/S(G)CLi) = > 1 - 1.38

N acute (CAT 1) Sum = Sum(Ci/M(acute)i\*25) = 0.048 - 0.072

# SECTION 4: First aid measures

#### 4.1. Description of first aid measures

#### **General information**

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. The doctor can contact The National Poisons Information Service: Dial 0344 892 0111 (24 h service). Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

#### **Inhalation**

Bring the person into fresh air and stay with him/her.

#### Skin contact

Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with soap and water.

### **Eve contact**



Remove contact lenses. Flush eyes immediately with plenty of water or isotonic water (20-30°C) for at least 5 minutes and continue until irritation stops. Make sure to flush under the upper and lower eyelids. If irritation continues, contact a doctor. Continue flushing during transport.

#### Ingestion

Provide plenty of water for the person to drink and stay with him/her. In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the victim lean forward with head down to avoid inhalation of or choking on vomited material.

#### **Burns**

Not applicable

### 4.2. Most important symptoms and effects, both acute and delayed

This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: headache, dizziness, ringing in ears, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

### 4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned: Get immediate medical advice/attention.

#### Information to medics

Bring this safety data sheet.

### **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

Recommended: alcohol-resistant foam, carbonic acid, powder, water mist.

# 5.2. Special hazards arising from the substance or mixture

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous catabolic substances are produced. These are: Carbon oxides. Fire will result in dense black smoke. Exposure to combustion products may harm your health. Fire fighters should wear appropriate protection equipment. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

### 5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

### SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

No specific requirements.

# 6.2. Environmental precautions

No specific requirements.

### 6.3. Methods and material for containment and cleaning up

Use sand, sawdust, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations.

#### 6.4. Reference to other sections

See section on "Disposal considerations" in regard of handling of waste. See section on 'Exposure controls/personal protection' for protective measures.

#### **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Smoking, storage of tobacco, consumption and storage of food or liquids are not allowed in the workrooms. See section on 'Exposure controls/personal protection' for information on personal protection.

#### 7.2. Conditions for safe storage, including any incompatibilities

Always store in containers of the same material as the original container. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

### Storage temperature

No data available.

### 7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2

### **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

#### **OEL**

propan-2-ol

Long-term exposure limit (8-hour TWA reference period): 400 ppm | 999 mg/m³ Short-term exposure limit (15-minute reference period): 500 ppm | 1250 mg/m³

#### **DNEL / PNEC**

DNEL (propan-2-ol): 319 mg/kg

Exposure: Dermal

Duration of Exposure: Long term – Systemic effects - General population

DNEL (propan-2-ol): 89 mg/m3

Exposure: Inhalation

Duration of Exposure: Long term – Systemic effects - General population

DNEL (propan-2-ol): 26 mg/kg

Exposure: Oral

Duration of Exposure: Long term - Systemic effects - General population

PNEC (propan-2-ol): 552 mg/kg dw Exposure: Marine water sediment

PNEC (propan-2-ol): 140,9 mg/l

Exposure: Freshwater

PNEC (propan-2-ol): 28 mg/kg dw

Exposure: Soil

PNEC (propan-2-ol): 140,9 mg/l Exposure: Marine water

PNEC (propan-2-ol): 140,9 mg/l Exposure: Intermittent release

PNEC (propan-2-ol): 2251 mg/l Exposure: Sewage Treatment Plant

PNEC (propan-2-ol): 552 mg/kg dw Exposure: Freshwater sediment

### 8.2. Exposure controls

Compliance with the accepted occupational exposure limits values should be controlled on a regular basis.

### **General recommendations**

Observe general occupational hygiene standards.

#### **Exposure scenarios**

In the event exposure scenarios are appended to the safety data sheet, the operational conditions and risk management measures in these shall be complied with.

### **Exposure limits**

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

### Appropriate technical measures

Installation of an exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure emergency eyewash and -showers are clearly marked.

#### **Hygiene measures**

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

#### Measures to avoid environmental exposure

No specific requirements.

### Individual protection measures, such as personal protective equipment





#### **Generally**

Use only CE marked protective equipment.

### **Respiratory Equipment**

If ventilation at the work place is insufficient, use a half- or full mask with an appropriate filter or an airsupplied breathing apparatus depending on the specific work situation and how long you will be using the product.

#### Skin protection

Dedicated work clothing should be worn.

#### **Hand protection**

Nitrile rubber

Breakthrough time: > 480 minutes (Class 6)

### **Eye protection**

Wear safety glasses with side shields.

### **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Form Liquid Colour White Odour Mild

Odour threshold (ppm) No data available.

Η 8

Viscosity (40°C)

Density (g/cm³)

No data available.

No data available.

Phase changes

Melting point (°C)

No data available.

Boiling point (°C) 100

Vapour pressure

Decomposition temperature (°C)

Evaporation rate (n-butylacetate = 100)

No data available.

No data available.

No data available.

Data on fire and explosion hazards

Flash point (°C)

Ignition (°C)

Auto flammability (°C)

Explosion limits (% v/v)

Explosive properties

No data available.

No data available.

No data available.

No data available.

**Solubility** 

Solubility in water Soluble

n-octanol/water coefficient No data available.

9.2. Other information

Solubility in fat (g/L) No data available.

# **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

No data available

### 10.2. Chemical stability

The product is stable under the conditions, noted in the section "Handling and storage".

## 10.3. Possibility of hazardous reactions

Nothing special

# 10.4. Conditions to avoid

Nothing special

### 10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

### 10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

# **SECTION 11: Toxicological information**

# 11.1. Information on toxicological effects

**Acute toxicity** 



Substance: Alcohols (C16-18) ethoxylated

Species: Rat Test: LD50

Route of exposure: Oral Result: 2000mg/kg

Substance: propan-2-ol

Species: Rat Test: LD50

Route of exposure: Oral Result: 5840 mg/kg

Substance: propan-2-ol

Species: Rat Test: LC50

Route of exposure: Inhalation

Result: 10000 ppm/6h

Substance: propan-2-ol Species: Rabbit Test: LD50

Route of exposure: Dermal

Result: 16,4 ml/kg

No data available.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

No data available.

Germ cell mutagenicity

No data available.

Carcinogenicity

No data available.

Reproductive toxicity

No data available.

STOT-single exposure

No data available.

STOT-repeated exposure

No data available.

**Aspiration hazard** 

No data available.

#### Long term effects

This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: headache, dizziness, ringing in ears, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure. This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

### **SECTION 12: Ecological information**

#### 12.1. Toxicity

Substance: Alcohols (C16-18) ethoxylated

Species: Daphnia Test: EC50 Duration: 48h Result: 0,1-1mg/l

Substance: propan-2-ol

Species: Fish Test: LC50 Duration: 96h Result: >100 mg/l

Substance: propan-2-ol Species: Daphnia Test: LC50 Duration: 48h Result: >100 mg/l

Substance: propan-2-ol Species: Algae

Test: EC50
Duration: 72h
Result: >100mg/l



12.2. Persistence and degradability

Substance Biodegradability Test Result

propan-2-ol No data available No data available

12.3. Bioaccumulative potential

Potential bioaccumulation LoaPow **BCF** Substance

Alcohols (C16-18) ethoxylated No data available No data available propan-2-ol No No data available

12.4. Mobility in soil

propan-2-ol: Log Koc= 0.117995, Calculated from LogPow (High mobility potential.).

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

12.6. Other adverse effects

This product contains substances that are toxic to the environment. May result in adverse effects to aquatic organisms.

#### **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Product is not covered by regulations on dangerous waste.

#### Waste

**EWC** code

# Specific labelling

Not applicable

#### Contaminated packing

Contaminated packaging must be disposed of similarly to the product.

### **SECTION 14: Transport information**

### 14.1 - 14.4

Not dangerous goods according to ADR, IATA and IMDG.

#### ADR/RID

14.1. UN number 14.2. UN proper shipping name

14.3. Transport hazard class(es)

14.4. Packing group

**Notes** 

**Tunnel restriction code** 

#### **IMDG**

UN-no.

**Proper Shipping Name** 

Class PG\*

**EmS** 

**Hazardous constituent** 

# IATA/ICAO

UN-no.

**Proper Shipping Name** Class

PG\*

#### 14.5. Environmental hazards

### 14.6. Special precautions for user

# 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available

- (\*) Packing group
- (\*\*) Marine pollutant

### **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **Restrictions for application**

People under the age of 18 shall not be exposed to this product cf. Council Directive 94/33/EC of 22 June



1994 on the protection of young people at work.

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

#### **Demands for specific education**

#### **Additional information**

Not applicable

#### Seveso

Biocidal reg. no.

Not applicable

#### Sources

Council Directive 94/33/EC of 22 June 1994 on the protection of young people at work.

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677. The Stationery Office, 2002.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (CLP). Regulation (EC) 1907/2006 (REACH).

### 15.2. Chemical safety assessment

No

### Skin corrosion/irritationSECTION 16: Other information

#### Full text of H-phrases as mentioned in section 3

H225 - Highly flammable liquid and vapour.

H302 - Harmful if swallowed.

H319 - Causes serious eye irritation.

H336 - May cause drowsiness or dizziness.

H400 - Very toxic to aquatic life.

#### The full text of identified uses as mentioned in section 1

#### **Additional label elements**

Not applicable

#### Other

In accordance with Regulation (EC) No. 1272/2008 (CLP) the evaluation of the classification of the mixture is based on:

The classification of the mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP)

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

### The safety data sheet is validated by

David Löwenstein

Date of last essential change (First cipher in SDS version)

Date of last minor change (Last cipher in SDS version)

ALPHAOMEGA. Licens nr.:3830228684, 7.0.1.11

www.chymeia.com