

SAFETY DATA SHEET
SECTION 1: Identification of the substance/mixture and of the company/undertaking
1.1. Product identifier
Trade name Print Wash 85 DK Product no.
REACH registration number Not applicable 1.2. Relevant identified uses of the substance or mixture and uses advised against
Relevant identified uses of the substance or mixture Washing liquid for the graphic industry Uses advised against
The full text of any mentioned and identified use categories are given in section 16 1.3. Details of the supplier of the safety data sheet
Company and address Blue & Green AB Stenorsvägen 52 261 44 Landskrona Sweden Tfn: +46 418 399000 Fax: +46 418 13199 www.blueandgreen.se E-mail info@blueandgreen.se
 SDS date 2020-11-11 SDS Version 1.0 1.4. Emergency telephone number Contact The National Poisons Information Service (dial 111, 24 h service). See section 4 "First aid measures".
SECTION 2: Hazards identification
2.1. Classification of the substance or mixture Not classified according to Regulation (EC) No. 1272/2008 (CLP)
2.2. Label elements Hazard pictogram(s) Not applicable Signal word
Hazard statement(s) Not applicable Precautionary statements General - Prevention - Response - Storage - Disposal -
Identity of the substances primarily responsible for the major health hazards Not applicable Additional labelling



Safety data sheet available	
Unique formula identifier (UF	FI)
4Q78-QU74-C10Y-K3KM	
2.3. Other hazards	
Not applicable	
Additional warnings	
Not applicable	
VOC (volatile organic compo	und)
Not applicable	
SECTION 3: Composition/information	n on ingredients
3.1/3.2. Substances/Mixtures	
NAME: IDENTIFICATION NOS.: CONTENT: CLP CLASSIFICATION:	1-(1-methyl-2-propoxyethoxy)propan-2-ol CAS-no: 29911-27-1 EC-no: 249-949-4 REACH-no: 01-2119908226-42 80-95% NA
NAME: IDENTIFICATION NOS.: CONTENT: CLP CLASSIFICATION: NOTE:	(2-methoxymethylethoxy)propanol CAS-no: 34590-94-8 EC-no: 252-104-2 REACH-no: 01-2119450011-60 10 - <15% O L
NAME: IDENTIFICATION NOS.: CONTENT: CLP CLASSIFICATION: NOTE:	2-(2-butoxyethoxy)ethanol CAS-no: 112-34-5 EC-no: 203-961-6 REACH-no: 01-2119475104-44 Index-no: 603-096-00-8 5 - <10% Eye Irrit. 2 H319 L
NAME: IDENTIFICATION NOS.: CONTENT: CLP CLASSIFICATION:	Distillates (petroleum), hydrotreated light CAS-no: 64742-47-8 EC-no: 265-149-8 REACH-no: 01-2119485032-45 Index-no: 649-422-00-2 1 - <2.5% Asp. Tox. 1, H304

(*) O = Organic solvent L = European occupational exposure limit. See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

Eye Cat. 2 Sum = Sum(Ci/S(G)CLi) = 0.4 - 0.6

Detergent:

< 5%: ALIPHATIC HYDROCARBONS, ANIONIC SURFACTANTS, AROMATIC HYDROCARBONS

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. The doctor can contact The National Poisons Information Service: Dial 0344 892 0111 (24 h service). Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Bring the person into fresh air and stay with him/her.

Skin contact

Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with soap and water.

Eye contact

Flush eyes with plenty of water (20-30°C) and continue until irritation stops.

Ingestion

Provide plenty of water for the person to drink and stay with him/her. In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the victim lean forward with head down to avoid inhalation of- or choking on vomited material.



Burns
Not applicable
4.2. Most important symptoms and effects, both acute and delayed
Nothing special
4.3. Indication of any immediate medical attention and special treatment needed
Nothing special
Information to medics
Bring this safety data sheet.
SECTION 5: Firefighting measures
5.1. Extinguishing media
Recommended: alcohol-resistant foam, carbonic acid, powder, water mist.
5.2. Special hazards arising from the substance or mixture
If the product is exposed to high temperatures, e.g. in the event of fire, dangerous catabolic substances are
produced. These are: Carbon oxides. Fire will result in dense black smoke. Exposure to combustion
products may harm your health. Fire fighters should wear appropriate protection equipment. Closed
containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to
enter the sewage system and nearby surface waters.
5.3. Advice for firefighters
Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure
contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.
SECTION 6: Accidental release measures
6.1. Personal precautions, protective equipment and emergency procedures
No specific requirements.
6.2. Environmental precautions
No specific requirements.
6.3. Methods and material for containment and cleaning up
Use sand, sawdust, earth, vermiculite, diatomaceous earth to contain and collect non-combustible
absorbent materials and place in container for disposal, according to local regulations.
6.4. Reference to other sections
See section on "Disposal considerations" in regard of handling of waste. See section on 'Exposure
controls/personal protection' for protective measures.
SECTION 7: Handling and storage
7.1. Precautions for safe handling
See section on 'Exposure controls/personal protection' for information on personal protection.
7.2. Conditions for safe storage, including any incompatibilities
Always store in containers of the same material as the original container.
Storage temperature
Room temperature 18 to 23°C
7.3. Specific end use(s)
This product should only be used for applications quoted in section 1.2
SECTION 8: Exposure controls/personal protection
SECTION 8: Exposure controls/personal protection 8.1. Control parameters
SECTION 8: Exposure controls/personal protection
SECTION 8: Exposure controls/personal protection 8.1. Control parameters OEL 2-(2-butoxyethoxy)ethanol Long-term exposure limit (8-hour TWA reference period): 10 ppm 67,5 mg/m ³
SECTION 8: Exposure controls/personal protection 8.1. Control parameters OEL 2-(2-butoxyethoxy)ethanol
SECTION 8: Exposure controls/personal protection 8.1. Control parameters OEL 2-(2-butoxyethoxy)ethanol Long-term exposure limit (8-hour TWA reference period): 10 ppm 67,5 mg/m ³ Short-term exposure limit (15-minute reference period): 15 ppm 101.2 mg/m ³
SECTION 8: Exposure controls/personal protection 8.1. Control parameters OEL 2-(2-butoxyethoxy)ethanol Long-term exposure limit (8-hour TWA reference period): 10 ppm 67,5 mg/m ³ Short-term exposure limit (15-minute reference period): 15 ppm 101.2 mg/m ³ (2-methoxymethylethoxy)propanol Long-term exposure limit (8-hour TWA reference period): 50 ppm 308 mg/m ³
SECTION 8: Exposure controls/personal protection 8.1. Control parameters OEL 2-(2-butoxyethoxy)ethanol Long-term exposure limit (8-hour TWA reference period): 10 ppm 67,5 mg/m ³ Short-term exposure limit (15-minute reference period): 15 ppm 101.2 mg/m ³ (2-methoxymethylethoxy)propanol Long-term exposure limit (8-hour TWA reference period): 50 ppm 308 mg/m ³ Short-term exposure limit (15-minute reference period): 50 ppm 308 mg/m ³
SECTION 8: Exposure controls/personal protection 8.1. Control parameters OEL 2-(2-butoxyethoxy)ethanol Long-term exposure limit (8-hour TWA reference period): 10 ppm 67,5 mg/m³ Short-term exposure limit (15-minute reference period): 15 ppm 101.2 mg/m³ (2-methoxymethylethoxy)propanol Long-term exposure limit (8-hour TWA reference period): 50 ppm 308 mg/m³ Short-term exposure limit (15-minute reference period): 50 ppm 308 mg/m³ Short-term exposure limit (15-minute reference period): 50 ppm 308 mg/m³ Short-term exposure limit (15-minute reference period): 50 ppm 308 mg/m³ Short-term exposure limit (15-minute reference period): 50 ppm 308 mg/m³ Short-term exposure limit (15-minute reference period): 50 ppm 308 mg/m³ Comments: Sk (Sk = Can be absorbed through skin.)
SECTION 8: Exposure controls/personal protection 8.1. Control parameters OEL 2-(2-butoxyethoxy)ethanol Long-term exposure limit (8-hour TWA reference period): 10 ppm 67,5 mg/m ³ Short-term exposure limit (15-minute reference period): 15 ppm 101.2 mg/m ³ (2-methoxymethylethoxy)propanol Long-term exposure limit (8-hour TWA reference period): 50 ppm 308 mg/m ³ Short-term exposure limit (15-minute reference period): 50 ppm 308 mg/m ³ Short-term exposure limit (15-minute reference period): - ppm - mg/m ³ Comments: Sk (Sk = Can be absorbed through skin.) DNEL / PNEC DNEL (2-(2-butoxyethoxy)ethanol): 83 mg/kg
SECTION 8: Exposure controls/personal protection 8.1. Control parameters OEL 2-(2-butoxyethoxy)ethanol Long-term exposure limit (8-hour TWA reference period): 10 ppm 67,5 mg/m ³ Short-term exposure limit (15-minute reference period): 15 ppm 101.2 mg/m ³ (2-methoxymethylethoxy)propanol Long-term exposure limit (8-hour TWA reference period): 50 ppm 308 mg/m ³ Short-term exposure limit (15-minute reference period): 50 ppm 308 mg/m ³ Short-term exposure limit (15-minute reference period): - ppm - mg/m ³ Comments: Sk (Sk = Can be absorbed through skin.) DNEL (2-(2-butoxyethoxy)ethanol): 83 mg/kg Exposure: Dermal
SECTION 8: Exposure controls/personal protection 8.1. Control parameters OEL 2-(2-butoxyethoxy)ethanol Long-term exposure limit (8-hour TWA reference period): 10 ppm 67,5 mg/m ³ Short-term exposure limit (15-minute reference period): 15 ppm 101.2 mg/m ³ (2-methoxymethylethoxy)propanol Long-term exposure limit (8-hour TWA reference period): 50 ppm 308 mg/m ³ Short-term exposure limit (15-minute reference period): 50 ppm 308 mg/m ³ Short-term exposure limit (15-minute reference period): - ppm - mg/m ³ Comments: Sk (Sk = Can be absorbed through skin.) DNEL / PNEC DNEL (2-(2-butoxyethoxy)ethanol): 83 mg/kg
SECTION 8: Exposure controls/personal protection 8.1. Control parameters OEL 2-(2-butoxyethoxy)ethanol Long-term exposure limit (8-hour TWA reference period): 10 ppm 67,5 mg/m ³ Short-term exposure limit (15-minute reference period): 15 ppm 101.2 mg/m ³ (2-methoxymethylethoxy)propanol Long-term exposure limit (8-hour TWA reference period): 50 ppm 308 mg/m ³ Short-term exposure limit (15-minute reference period): - ppm - mg/m ³ Comments: Sk (Sk = Can be absorbed through skin.) DNEL / PNEC DNEL (2-(2-butoxyethoxy)ethanol): 83 mg/kg Exposure: Dermal Duration of Exposure: Long term – Systemic effects - Workers DNEL (2-(2-butoxyethoxy)ethanol): 67.5 mg/m3
SECTION 8: Exposure controls/personal protection 8.1. Control parameters OEL 2-(2-butoxyethoxy)ethanol Long-term exposure limit (8-hour TWA reference period): 10 ppm 67,5 mg/m ³ Short-term exposure limit (15-minute reference period): 15 ppm 101.2 mg/m ³ (2-methoxymethylethoxy)propanol Long-term exposure limit (8-hour TWA reference period): 50 ppm 308 mg/m ³ Short-term exposure limit (15-minute reference period): - ppm - mg/m ³ Comments: Sk (Sk = Can be absorbed through skin.) DNEL / PNEC DNEL (2-(2-butoxyethoxy)ethanol): 83 mg/kg Exposure: Dermal Duration of Exposure: Long term – Systemic effects - Workers



DNEL (2-(2-butoxyethoxy)ethanol): 67.5 mg/m3 Exposure: Inhalation Duration of Exposure: Long term – Local effects - Workers

DNEL (2-(2-butoxyethoxy)ethanol): 5 mg/kg bw/d Exposure: Oral Duration of Exposure: Long term – Systemic effects - General population

DNEL (2-(2-butoxyethoxy)ethanol): 50 mg/kg bw/d Exposure: Dermal Duration of Exposure: Long term – Systemic effects - General population

DNEL (2-(2-butoxyethoxy)ethanol): 40.5 mg/m3 Exposure: Inhalation Duration of Exposure: Long term – Local effects - General population

DNEL (2-(2-butoxyethoxy)ethanol): 101.2 mg/m3 Exposure: Inhalation Duration of Exposure: Short term – Local effects - Workers

DNEL (2-(2-butoxyethoxy)ethanol): 40.5 mg/m3 Exposure: Inhalation Duration of Exposure: Long term – Systemic effects - General population

DNEL (2-(2-butoxyethoxy)ethanol): 60.7 mg/m3 Exposure: Inhalation Duration of Exposure: Short term – Local effects - General population

DNEL ((2-methoxymethylethoxy)propanol): 283 mg/kg bw/day Exposure: Dermal Duration of Exposure: Long term – Systemic effects - Workers

DNEL ((2-methoxymethylethoxy)propanol): 308 mg/kg Exposure: Inhalation Duration of Exposure: Long term – Systemic effects - Workers

DNEL ((2-methoxymethylethoxy)propanol): 121 mg/kg bw/day Exposure: Dermal Duration of Exposure: Long term – Systemic effects - General population

DNEL ((2-methoxymethylethoxy)propanol): 37.2 mg/m3 Exposure: Inhalation Duration of Exposure: Long term – Systemic effects - General population

DNEL ((2-methoxymethylethoxy)propanol): 36 mg/kg bw/day Exposure: Oral Duration of Exposure: Long term – Systemic effects - General population

DNEL (1-(1-methyl-2-propoxyethoxy)propan-2-ol): 60mg/kg Exposure: Dermal

Duration of Exposure: Long term - Systemic effects - Workers

DNEL (1-(1-methyl-2-propoxyethoxy)propan-2-ol): 84mg/m3 Exposure: Inhalation Duration of Exposure: Long term – Systemic effects - Workers

DNEL (1-(1-methyl-2-propoxyethoxy)propan-2-ol): 30mg/kg Exposure: Dermal

Duration of Exposure: Long term - Systemic effects - General population

DNEL (1-(1-methyl-2-propoxyethoxy)propan-2-ol): 21mg/m3 Exposure: Inhalation Duration of Exposure: Long term – Systemic effects - General population

DNEL (1-(1-methyl-2-propoxyethoxy)propan-2-ol): 6mg/kg Exposure: Oral Duration of Exposure: Long term – Systemic effects - General population

PNEC (2-(2-butoxyethoxy)ethanol): 200 mg/l Exposure: Sewage Treatment Plant



According to E

Skin protection

ording to EC-Regulation 2015/830	Quality chemicals
PNEC (2-(2-butoxyethoxy)ethanol): 0.44 mg/kg dw Exposure: Marine water sediment	
PNEC (2-(2-butoxyethoxy)ethanol): 4.4 mg/kg dw Exposure: Freshwater sediment	
PNEC (2-(2-butoxyethoxy)ethanol): 1 mg/l Exposure: Freshwater	
PNEC (2-(2-butoxyethoxy)ethanol): 0.1 mg/l Exposure: Marine water	
PNEC (2-(2-butoxyethoxy)ethanol): 3.9 mg/l Exposure: Intermittent release	
PNEC (2-(2-butoxyethoxy)ethanol): 0.32 mg/kg dw Exposure: Soil	
PNEC ((2-methoxymethylethoxy)propanol): 19 mg/l Exposure: Freshwater	
PNEC ((2-methoxymethylethoxy)propanol): 1.9 mg/l Exposure: Marine water	
PNEC ((2-methoxymethylethoxy)propanol): 190 mg/l Exposure: Intermittent release	
PNEC ((2-methoxymethylethoxy)propanol): 70.2 mg/kg/dwt Exposure: Freshwater sediment	
PNEC ((2-methoxymethylethoxy)propanol): 7.02 mg/kg/dwt Exposure: Marine water sediment	
PNEC ((2-methoxymethylethoxy)propanol): 2.74 mg/kg Exposure: Soil	
 PNEC ((2-methoxymethylethoxy)propanol): 4168 mg/l Exposure: Sewage Treatment Plant 8.2. Exposure controls Compliance with the accepted occupational exposure limits values should be of General recommendations Smoking, eating and drinking are not allowed in the work premises Exposure scenarios There is no appendix to this safety data sheet. 	ontrolled on a regular basis.
Exposure limits Professional users are subjected to the legally set maximum concentrations for occupational hygiene limit values above.	⁻ occupational exposure. See
Appropriate technical measures Ensure emergency eyewash and -showers are clearly marked. Hygiene measures	
In between use of the product and at the end of the working day all exposed ar washed thoroughly. Always wash hands, forearms and face. Measures to avoid environmental exposure	eas of the body must be
No specific requirements. Individual protection measures, such as personal protective equipment	
Generally	
Use only CE marked protective equipment.	
Respiratory Equipment	
NA	



According to EC-Regulation 2015/830	
Dedicated work clothing should be worn.	
Hand protection	
4H/Barrier	
Breakthrough time: See the manufacturer's instructions.	
Eye protection	
Wear safety glasses with side shields.	
SECTION 9: Physical and chemical properties	
9.1. Information on basic physical and chemical propertie	S
Form	Liquid
Colour	Colourless
Odour	Characteristic
Odour threshold (ppm)	No data available.
pH	No data available.
Viscosity (40°C)	No data available.
Density (g/cm ³)	No data available.
Phase changes	
Melting point (°C)	No data available.
Boiling point (°C)	No data available.
Vapour pressure	No data available.
Decomposition temperature (°C)	No data available.
Evaporation rate (n-butylacetate = 100)	No data available.
Data on fire and explosion hazards	
Flash point (°C)	No data available.
Ignition (°C)	No data available.
Auto flammability (°C)	No data available.
Explosion limits (% v/v)	No data available.
Explosive properties	No data available.
	No data avaliable.
Solubility Solubility in water	Inaclubia
Solubility in water	Insoluble
n-octanol/water coefficient	No data available.
9.2. Other information	
Solubility in fat (g/L)	No data available.
SECTION 10: Stability and reactivity	
10.1. Reactivity	
No data available	
10.2. Chemical stability	agetion "Handling and storage"
The product is stable under the conditions, noted in the	Section manuling and storage.
10.3. Possibility of hazardous reactions	
Nothing special	
10.4. Conditions to avoid	
Nothing special	
10.5. Incompatible materials	
Strong acids, strong bases, strong oxidizing agents, and	d strong reducing agents.
10.6. Hazardous decomposition products	
The product is not degraded when used as specified in	section 1.
SECTION 11: Toxicological information	
11.1. Information on toxicological effects	
Acute toxicity Substance: Distillates (petroleum), hydrotreated light	
Substance: Distillates (petroleum), hydrotreated light Species: Rat	
Test: LD50	
Route of exposure: Dermal	
Result: >2000mg/kg	
Cubatanana Dis (llatana (natural acces) da	
Substance: Distillates (petroleum), hydrotreated light	
Species: Rabbit	
Species: Rabbit Test: LD50	



Route of exposure: Dermal Result: >2000mg/kg

Substance: Distillates (petroleum), hydrotreated light Species: Rat Test: LD50 Route of exposure: Oral Result: >5000mg/kg

Substance: Distillates (petroleum), hydrotreated light Species: Rat Test: LC50 Route of exposure: Inhalation Result: >4950mg/m3 4h

Substance: 2-(2-butoxyethoxy)ethanol Species: Rabbit Test: LD50 Route of exposure: Dermal Result: 2764 mg/kg

Substance: 2-(2-butoxyethoxy)ethanol Species: Mouse Test: LD50 Route of exposure: Oral Result: 2410 mg/kg

Substance: 2-(2-butoxyethoxy)ethanol Species: Rat Test: LD50 Route of exposure: Oral Result: >2000 mg/kg

Substance: 2-(2-butoxyethoxy)ethanol Species: Rat Test: LC50 Route of exposure: Inhalation Result: >29 ppm 2h

Substance: (2-methoxymethylethoxy)propanol Species: Rabbit Test: LD50 Route of exposure: Dermal Result: 9510 mg/kg

Substance: (2-methoxymethylethoxy)propanol Species: Rat Test: LD50 Route of exposure: Oral Result: 5000 mg/kg

Substance: (2-methoxymethylethoxy)propanol Species: Rat Test: LC50 Route of exposure: Inhalation Result: 3.35 mg/l 7h ånga

Substance: 1-(1-methyl-2-propoxyethoxy)propan-2-ol Species: Rat Test: LD50 Route of exposure: Dermal Result: 2000mg/kg

Substance: 1-(1-methyl-2-propoxyethoxy)propan-2-ol Species: Rat Test: LD50 Route of exposure: Oral Result: 2000mg/kg Skin corrosion/irritation Data on substance: 2-(2-butoxyethoxy)ethanol Test: OECD Guideline 404

Organism: Rabbit Result: not irritating



Serious eye damage/irritation Data on substance: 2-(2-butoxyethoxy)ethanol Test: OECD Guideline 404 Organism: Rabbit Result: irritating Respiratory or skin sensitisation Data on substance: 2-(2-butoxyethoxy)ethanol Test: OECD Guideline 406 Organism: Guinea pig Result: Negative Germ cell mutagenicity No data available. Carcinogenicity No data available. **Reproductive toxicity** No data available. STOT-single exposure No data available. STOT-repeated exposure No data available. Aspiration hazard No data available. Long term effects Nothing special **SECTION 12: Ecological information** 12.1. Toxicity Substance: Distillates (petroleum), hydrotreated light Species: Daphnia Test: EC50 Duration: 48h Result: >1000mg/l Substance: Distillates (petroleum), hydrotreated light Species: Fish Test: LC50 Duration: 24h Result: >1000mg/l Substance: Distillates (petroleum), hydrotreated light Species: Algae Test: EC50 Duration: 72h Result: >1000mg/l Substance: 2-(2-butoxyethoxy)ethanol Species: Daphnia Test: EC50 Duration: 48h Result: >100 mg/l Substance: 2-(2-butoxyethoxy)ethanol Species: Fish Test: LC50 Duration: 96h Result: >100 mg/l Substance: 2-(2-butoxyethoxy)ethanol Species: Algae Test: EC50 Duration: 96h Result: >100 mg/l Substance: (2-methoxymethylethoxy)propanol Species: Daphnia Test: NOEC Duration: 22d Result: 0.5 mg/l Substance: (2-methoxymethylethoxy)propanol Species: Daphnia Test: EC50 Duration: 48h



A

According to EC-Regulation 2015/830			
Result: 1919 mg/l			
Substance: (2-methoxymethylethoxy)pro Species: Fish Test: LC50 Duration: 96h Result: >1000 mg/l	opanol		
Substance: (2-methoxymethylethoxy)pro Species: Algae Test: EC50 Duration: 72h Result: 969 mg/l	opanol		
Substance: 1-(1-methyl-2-propoxyethoxy Species: Daphnia Test: EC50 Duration: 48h Result: >100mg/l	y)propan-2-ol		
Substance: 1-(1-methyl-2-propoxyethoxy Species: Fish Test: LC50 Duration: 96h Result: >100mg/l	/)propan-2-ol		
Substance: 1-(1-methyl-2-propoxyethoxy Species: Algae Test: EC50 Duration: Result: >1000mg/l	y)propan-2-ol		
12.2. Persistence and degradability Substance	Biodegradability	Test	Result
2-(2-butoxyethoxy)ethanol (2-methoxymethylethoxy)propano 1-(1-methyl-2-propoxyethoxy)pr	Yes Yes	Modified OECD Screening Test DOC Die-Away Test DOC Die-Away Test	100% 75% 92%
12.3. Bioaccumulative potential			
Substance 2-(2-butoxyethoxy)ethanol (2-methoxymethylethoxy)propano 1-(1-methyl-2-propoxyethoxy)pr	Potential bioaccumulation No No No	LogPow 1 0.006 0.88	BCF No data available No data available No data available
(2-methoxymethylethoxy)propano: Log 1-(1-methyl-2-propoxyethoxy)pr: Log k	Coc= 2.8 (Moderate mobility potential.).	potential.).	
12.6. Other adverse effects Nothing special	ny substances considered to meet the criteria	classifying them as PBT a	nd/or vPvB.
SECTION 13: Disposal considerations			
13.1. Waste treatment methods Product is not covered by regula Waste EWC code	tions on dangerous waste.		
- Specific labelling Not applicable Contaminated packing No specific requirements.			
SECTION 14: Transport information			
14.1 – 14.4 Not dangerous goods according ADR/RID 14.1. UN number	to ADR, IATA and IMDG.		



14.5. Environmental hazards

14.6. Special precautions for user

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available (*) Packing group

(**) Marine pollutant

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

People under the age of 18 shall not be exposed to this product cf. Council Directive 94/33/EC of 22 June 1994 on the protection of young people at work.

Demands for specific education

Additional information

Not applicable

Seveso

Biocidal reg. no.

Not applicable

Sources

Council Directive 92/85/EEC on the introduction of measures to encourage improvements in the safety and health at work of pregnant workers and workers who have recently given birth or are breastfeeding. Council Directive 94/33/EC of 22 June 1994 on the protection of young people at work.

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677. The Stationery Office, 2002.

Regulation (EC) No 648/2004 of the European Parliament and of the Council of 31 March 2004 on detergents.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (CLP). Regulation (EC) 1907/2006 (REACH).

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

H304 - May be fatal if swallowed and enters airways.

H319 - Causes serious eye irritation.



The full text of identified uses as mentioned in section 1

Additional label elements

Not applicable

Other

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The safety data sheet is validated by David Löwenstein Date of last essential change (First cipher in SDS version)

Date of last minor change (Last cipher in SDS version)

ALPHAOMEGA. Licens nr.:4030228872, Blue & Green AB, 7.0.1.11 www.chymeia.com