

# SAFETY DATA SHEET

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Trade name**

Screenwash Concentrate

**Product no.**

-

**REACH registration number**

Not applicable

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses of the substance or mixture**

Screen Wash

**Uses advised against**

-

The full text of any mentioned and identified use categories are given in section 16

### 1.3. Details of the supplier of the safety data sheet

**Company and address**

Blue & Green AB  
Stenorsvägen 52  
261 44 Landskrona  
Sweden  
Tfn: +46 418 399000  
Fax: +46 418 13199  
www.blueandgreen.se

**E-mail**

info@blueandgreen.se

**SDS date**

2020-08-31

**SDS Version**

1.0

### 1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service). See section 4 "First aid measures".

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

Flam. Liq. 2; H225

Eye Irrit. 2; H319

See full text of H-phrases in section 2.2.

### 2.2. Label elements

**Hazard pictogram(s)****Signal word**

Danger

**Hazard statement(s)**

Highly flammable liquid and vapour. (H225)

Causes serious eye irritation. (H319)

**Precautionary statements**

According to EC-Regulation 2015/830

<b>General</b>	If medical advice is needed, have product container or label at hand. (P101). Keep out of reach of children. (P102).
<b>Prevention</b>	Wear eye protection/gloves. (P280).
<b>Response</b>	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. (P305+P351+P338).
<b>Storage</b>	Store in a well-ventilated place. Keep cool. (P403+P235).
<b>Disposal</b>	Dispose of contents/container to an approved waste disposal plant. (P501).

**Identity of the substances primarily responsible for the major health hazards**

Not applicable

**Additional labelling**

Not applicable

**Unique formula identifier (UFI)**

AGTQ-RKN9-E007-KTY5

**2.3. Other hazards**

This product contains an organic solvent. Repeated or prolonged exposure to organic solvents may result in adverse effects to the nervous system and internal organs such as liver and kidneys.

**Additional warnings**

Tactile warning.

**VOC (volatile organic compound)**

Not applicable

**SECTION 3: Composition/information on ingredients**

**3.1/3.2. Substances/Mixtures**

NAME: ethanol  
 IDENTIFICATION NOS.: CAS-no: 64-17-5 EC-no: 200-578-6 REACH-no: 01-2119457610-43 Index-no: 603-002-00-5  
 CONTENT: 80-95%  
 CLP CLASSIFICATION: Flam. Liq. 2, Eye Irrit. 2  
 H225, H319  
 NOTE: O

NAME: ethanediol ethylene glycol  
 IDENTIFICATION NOS.: CAS-no: 107-21-1 EC-no: 203-473-3 REACH-no: 01-2119456816-28 Index-no: 603-027-00-1  
 CONTENT: 1 - <2.5%  
 CLP CLASSIFICATION: Acute Tox. 4, STOT RE 2  
 H302, H373  
 NOTE: O L

NAME: butanone  
 IDENTIFICATION NOS.: CAS-no: 78-93-3 EC-no: 201-159-0 REACH-no: 01-2119457290-43 Index-no: 606-002-00-3  
 CONTENT: 1 - <2.5%  
 CLP CLASSIFICATION: Flam. Liq. 2, STOT SE 3, Eye Irrit. 2  
 H225, H319, H336, EUH066  
 NOTE: O L

(\*) O = Organic solvent L = European occupational exposure limit. See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

**Other information**

ATEmix(inhale, vapour) > 20  
 ATEmix(oral) > 2000  
 Eye Cat. 2 Sum = Sum(Ci/S(G)CLi) = 7.32 - 10.98

Detergent:  
 > 30%: ALCOHOL

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

**General information**

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. The doctor can contact The National Poisons Information Service: Dial 0344 892 0111 (24 h service). Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

**Inhalation**

According to EC-Regulation 2015/830

Bring the person into fresh air and stay with him/her.

**Skin contact**

Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with soap and water.

**Eye contact**

Remove contact lenses. Flush eyes immediately with plenty of water or isotonic water (20-30°C) for at least 5 minutes and continue until irritation stops. Make sure to flush under the upper and lower eyelids. If irritation continues, contact a doctor. Continue flushing during transport.

**Ingestion**

Provide plenty of water for the person to drink and stay with him/her. In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the victim lean forward with head down to avoid inhalation of- or choking on vomited material.

**Burns**

Rinse with water until the pain stops then continue to rinse for a further 30 minutes.

**4.2. Most important symptoms and effects, both acute and delayed**

This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: headache, dizziness, ringing in ears, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

**4.3. Indication of any immediate medical attention and special treatment needed**

IF exposed or concerned: Get immediate medical advice/attention.

**Information to medics**

Bring this safety data sheet.

**SECTION 5: Firefighting measures**

**5.1. Extinguishing media**

Recommended: alcohol-resistant foam, carbonic acid, powder, water mist.

**5.2. Special hazards arising from the substance or mixture**

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous catabolic substances are produced. These are: Carbon oxides. Fire will result in dense black smoke. Exposure to combustion products may harm your health. Fire fighters should wear appropriate protection equipment. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

**5.3. Advice for firefighters**

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.

**6.2. Environmental precautions**

No specific requirements.

**6.3. Methods and material for containment and cleaning up**

Use sand, sawdust, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations.

**6.4. Reference to other sections**

See section on "Disposal considerations" in regard of handling of waste. See section on 'Exposure controls/personal protection' for protective measures.

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

Avoid static electricity. Protect electrical equipment in accordance with current standards. Do not use spark-forming tools.

Smoking, storage of tobacco, consumption and storage of food or liquids are not allowed in the workrooms. See section on 'Exposure controls/personal protection' for information on personal protection.

According to EC-Regulation 2015/830

### 7.2. Conditions for safe storage, including any incompatibilities

Always store in containers of the same material as the original container. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Must be stored in a cool and well-ventilated area, away from possible sources of ignition.

#### Storage temperature

No data available.

### 7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### OEL

butanone

Long-term exposure limit (8-hour TWA reference period): 200 ppm | 600 mg/m<sup>3</sup>

Short-term exposure limit (15-minute reference period): 300 ppm | 899 mg/m<sup>3</sup>

Comments: Sk; BMGV (Bmgv = Biological Monitoring Guidance Value. Sk = Can be absorbed through skin. )

ethanediol ethylene glycol

Long-term exposure limit (8-hour TWA reference period): 20(vapour) ppm | 10(par)/52(vap) mg/m<sup>3</sup>

Short-term exposure limit (15-minute reference period): 40 (vapour) ppm | 104 (vapour) mg/m<sup>3</sup>

Comments: Sk, par: particulate, vap: vapour (Sk = Can be absorbed through skin. )

ethanol

Long-term exposure limit (8-hour TWA reference period): 1000 ppm | 1920 mg/m<sup>3</sup>

Short-term exposure limit (15-minute reference period): - ppm | - mg/m<sup>3</sup>

#### DNEL / PNEC

DNEL (ethanol): 950mg/m<sup>3</sup>

Exposure: Inhalation

Duration of Exposure: Long term – Systemic effects - Workers

DNEL (ethanol): 343mg/kg/day

Exposure: Dermal

Duration of Exposure: Long term – Systemic effects - Workers

DNEL (ethanol): 950mg/m<sup>3</sup>

Exposure: Inhalation

Duration of Exposure: Short term – Local effects - General population

DNEL (ethanol): 87mg/kg/day

Exposure: Oral

Duration of Exposure: Long term – Systemic effects - General population

DNEL (ethanol): 114mg/m<sup>3</sup>

Exposure: Inhalation

Duration of Exposure: Long term – Systemic effects - General population

DNEL (ethanol): 206mg/kg/day

Exposure: Dermal

Duration of Exposure: Long term – Systemic effects - General population

DNEL (ethanol): 1900mg/m<sup>3</sup>

Exposure: Inhalation

Duration of Exposure: Short term – Local effects - Workers

DNEL (butanone): 106mg/m<sup>3</sup>

Exposure: Inhalation

Duration of Exposure: Long term – Systemic effects - General population

DNEL (butanone): 412mg/kg

Exposure: Dermal

Duration of Exposure: Long term – Systemic effects - General population

DNEL (butanone): 31mg/kg

Exposure: Oral

Duration of Exposure: Long term – Systemic effects - General population

DNEL (butanone): 600mg/m<sup>3</sup>

Exposure: Inhalation

Duration of Exposure: Long term – Systemic effects - Workers

According to EC-Regulation 2015/830

DNEL (butanone): 1161mg/kg  
Exposure: Dermal  
Duration of Exposure: Long term – Systemic effects - Workers

DNEL ( ethanediol ethylene glycol ): 35 mg/m3  
Exposure: Inhalation  
Duration of Exposure: Long term – Local effects - Workers  
Remarks: Registration dossier ECHA

DNEL ( ethanediol ethylene glycol ): 106 mg/kg bw/day  
Exposure: Dermal  
Duration of Exposure: Long term – Systemic effects - Workers  
Remarks: Registration dossier ECHA

DNEL ( ethanediol ethylene glycol ): 53 mg/kg bw/day  
Exposure: Dermal  
Duration of Exposure: Long term – Systemic effects - General population  
Remarks: Registration dossier ECHA

DNEL ( ethanediol ethylene glycol ): 7 mg/m3  
Exposure: Inhalation  
Duration of Exposure: Long term – Local effects - Workers  
Remarks: Registration dossier ECHA

PNEC (ethanol): 0,96mg/l  
Exposure: Freshwater

PNEC (ethanol): 0,79mg/l  
Exposure: Marine water

PNEC (ethanol): 2,75mg/l  
Exposure: Intermittent release

PNEC (ethanol): 3,6mg/kg  
Exposure: Freshwater sediment

PNEC (ethanol): 0,63mg/kg  
Exposure: Soil

PNEC (ethanol): 2,9mg/kg  
Exposure: Marine water sediment

PNEC (ethanol): 580mg/l  
Exposure: Sewage Treatment Plant

PNEC (butanone): 55,8mg/l  
Exposure: Marine water

PNEC (butanone): 55,8mg/l  
Exposure: Freshwater

PNEC (butanone): 22,5mg/kg  
Exposure: Soil

PNEC (butanone): 287,7mg/kg  
Exposure: Marine water sediment

PNEC (butanone): 284,74mg/kg  
Exposure: Freshwater sediment

PNEC (butanone): 709mg/l  
Exposure: Sewage Treatment Plant

PNEC (butanone): 55,8mg/l  
Exposure: Water

PNEC ( ethanediol ethylene glycol ): 1,53 mg/kg  
Exposure: Soil  
Remarks: Registration dossier ECHA

PNEC ( ethanediol ethylene glycol ): 3,7 mg/kg dw  
Exposure: Marine water sediment  
Remarks: Registration dossier ECHA

According to EC-Regulation 2015/830

PNEC ( ethanediol ethylene glycol ): 37 mg/kg dw  
Exposure: Freshwater sediment  
Remarks: Registration dossier ECHA

PNEC ( ethanediol ethylene glycol ): 199,5 mg/l  
Exposure: Sewage Treatment Plant  
Remarks: Registration dossier ECHA

PNEC ( ethanediol ethylene glycol ): 10 mg/l  
Exposure: Freshwater  
Remarks: Registration dossier ECHA

PNEC ( ethanediol ethylene glycol ): 1 mg/l  
Exposure: Marine water  
Remarks: Registration dossier ECHA

## 8.2. Exposure controls

Compliance with the accepted occupational exposure limits values should be controlled on a regular basis.

### General recommendations

Observe general occupational hygiene standards.

### Exposure scenarios

There is no appendix to this safety data sheet.

### Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

### Appropriate technical measures

Ensure emergency eyewash and -showers are clearly marked.

### Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

### Measures to avoid environmental exposure

No specific requirements.

### Individual protection measures, such as personal protective equipment



### Generally

Use only CE marked protective equipment.

### Respiratory Equipment

Recommended: A. Class 1 (low capacity). Brown

### Skin protection

Wear appropriate protection clothing, e.g. coveralls in polypropylene approved type 6 and Category III.

### Hand protection

Butyl rubber

Can be reused after cleaning

### Eye protection

Wear safety glasses with side shields.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Form	Liquid
Colour	Blue
Odour	Alcohol odor
Odour threshold (ppm)	No data available.
pH	7
Viscosity (40°C)	No data available.
Density (g/cm <sup>3</sup> )	0.807
<b>Phase changes</b>	
Melting point (°C)	-114

According to EC-Regulation 2015/830

Boiling point (°C)	82
Vapour pressure	No data available.
Decomposition temperature (°C)	No data available.
Evaporation rate (n-butylacetate = 100)	No data available.
<b>Data on fire and explosion hazards</b>	
Flash point (°C)	16
Ignition (°C)	No data available.
Auto flammability (°C)	No data available.
Explosion limits (% v/v)	2 - 12.7
Explosive properties	No data available.
<b>Solubility</b>	
Solubility in water	Soluble
n-octanol/water coefficient	No data available.
<b>9.2. Other information</b>	
Solubility in fat (g/L)	No data available.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No data available

### 10.2. Chemical stability

The product is stable under the conditions, noted in the section "Handling and storage".

### 10.3. Possibility of hazardous reactions

Nothing special

### 10.4. Conditions to avoid

Avoid static electricity.

### 10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

### 10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute toxicity

Substance: butanone

Species: Rat

Test: LD50

Route of exposure: Oral

Result: >2000-<5000mg/kg

Substance: butanone

Species: Rabbit

Test: LD50

Route of exposure: Dermal

Result: >5000mg/kg

Substance: butanone

Species: Rabbit

Test: LC50

Route of exposure: Inhalation

Result: >5000ppm

Substance: ethanediol ethylene glycol

Species: Rat

Test: LD50

Route of exposure: Oral

Result: >2000 mg/kg

Substance: ethanediol ethylene glycol

Species: Rabbit

Test: LD50

Route of exposure: Dermal

Result: >3500 mg/kg

Substance: ethanediol ethylene glycol

According to EC-Regulation 2015/830

Species: Mouse  
 Test: LC50  
 Route of exposure: Inhalation  
 Result: >2,5 mg/l 6h

Substance: ethanol  
 Species: Rat  
 Test: LD50  
 Route of exposure: Oral  
 Result: 10470mg/kg

Substance: ethanol  
 Species: Rat  
 Test: LC50  
 Route of exposure: Inhalation  
 Result: 200mg/l/4h

Substance: ethanol  
 Species: Rabbit  
 Test: LD lo  
 Route of exposure: Dermal  
 Result: >15800mg/kg

Substance: ethanol  
 Species: Human  
 Test: LD lo  
 Route of exposure: Oral  
 Result: 6000mg/kg

Substance: ethanol  
 Species: Rat  
 Test: LD50  
 Route of exposure: Dermal  
 Result: 15800mg/kg

**Skin corrosion/irritation**

No data available.

**Serious eye damage/irritation**

Causes serious eye irritation.

**Respiratory or skin sensitisation**

No data available.

**Germ cell mutagenicity**

No data available.

**Carcinogenicity**

No data available.

**Reproductive toxicity**

No data available.

**STOT-single exposure**

No data available.

**STOT-repeated exposure**

Data on substance: ethanediol ethylene glycol

Test: OECD 452

Duration of Exposure: 12 month

Organism: Rat

Target organ: Kidney

Result: 300 mg/kg bw/d

**Aspiration hazard**

No data available.

**Long term effects**

This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: headache, dizziness, ringing in ears, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

**SECTION 12: Ecological information**

**12.1. Toxicity**

Substance: butanone  
 Species: Fish  
 Test: LC50  
 Duration: 96h  
 Result: 2993mg/l

Substance: butanone



According to EC-Regulation 2015/830

Species: Algae  
 Test: EC50  
 Duration:  
 Result: 1888mg/l

Substance: butanone  
 Species: Daphnia  
 Test: EC50  
 Duration:  
 Result: 308mg/l

Substance: ethanediol ethylene glycol  
 Species: Fish  
 Test: LC50  
 Duration: 96h  
 Result: 72860 mg/l

Substance: ethanediol ethylene glycol  
 Species: Daphnia  
 Test: EC50  
 Duration: 48h  
 Result: 13900-57600 mg/l

Substance: ethanediol ethylene glycol  
 Species: Algae  
 Test: EC50  
 Duration: 72h  
 Result: 6500-13000 ml/l

Substance: ethanediol ethylene glycol  
 Species: Fish  
 Test: NOEC  
 Duration: 7d  
 Result: 15380 mg/l

Substance: ethanediol ethylene glycol  
 Species: Daphnia  
 Test: NOEC  
 Duration: 7d  
 Result: 8590 mg/l

Substance: ethanol  
 Species: Fish  
 Test: LC50  
 Duration: 96h  
 Result: 13500mg/l

Substance: ethanol  
 Species: Daphnia  
 Test: EC50  
 Duration: 48h  
 Result: 12,34mg/l

Substance: ethanol  
 Species: Algae  
 Test: IC50  
 Duration: 72h  
 Result: >10,9mg/l

**12.2. Persistence and degradability**

Substance	Biodegradability	Test	Result
ethanediol ethylene glycol	Yes	DOC Die-Away Test	90%
ethanol	Yes	Closed Bottle Test	85%

**12.3. Bioaccumulative potential**

Substance	Potential bioaccumulation	LogPow	BCF
ethanediol ethylene glycol	No	-1.36	No data available
ethanol	No	-0.31	0.66

**12.4. Mobility in soil**

ethanediol ethylene glycol : Log Koc= 1 (High mobility potential.).  
 ethanol: Log Koc= -0.167089, Calculated from LogPow (High mobility potential.).

**12.5. Results of PBT and vPvB assessment**

According to EC-Regulation 2015/830

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

### 12.6. Other adverse effects

Nothing special

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Product is covered by the regulations on hazardous waste.

#### Waste

EWC code

-

#### Specific labelling

Not applicable

#### Contaminated packing

Contaminated packaging must be disposed of similarly to the product.

## SECTION 14: Transport information

### 14.1 – 14.4

This product is within scope of the regulations of transport of dangerous goods.

#### ADR/RID

14.1. UN number	1993
14.2. UN proper shipping name	FLAMMABLE LIQUID, N.O.S.
14.3. Transport hazard class(es)	3
14.4. Packing group	II
Notes	-
Tunnel restriction code	D/E

#### IMDG

UN-no.	1993
Proper Shipping Name	FLAMMABLE LIQUID, N.O.S.
Class	3
PG*	II
EmS	F-E, S-E
MP**	No
Hazardous constituent	33

#### IATA/CAO

UN-no.	1993
Proper Shipping Name	FLAMMABLE LIQUID, N.O.S.
Class	3
PG*	II

### 14.5. Environmental hazards

-

### 14.6. Special precautions for user

-

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available

(\*) Packing group

(\*\*) Marine pollutant

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Restrictions for application

People under the age of 18 shall not be exposed to this product cf. Council Directive 94/33/EC of 22 June 1994 on the protection of young people at work.

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

#### Demands for specific education

-

#### Additional information

Not applicable

#### Seveso

Seveso III Part 1: P5c

According to EC-Regulation 2015/830

**Biocidal reg. no.**

Not applicable

**Sources**

Council Directive 92/85/EEC on the introduction of measures to encourage improvements in the safety and health at work of pregnant workers and workers who have recently given birth or are breastfeeding.

Council Directive 94/33/EC of 22 June 1994 on the protection of young people at work.

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677. The Stationery Office, 2002.

Regulation (EC) No 648/2004 of the European Parliament and of the Council of 31 March 2004 on detergents.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (CLP).

Regulation (EC) 1907/2006 (REACH).

The Control of Major Accident Hazards (COMAH) Regulations 2015.

**15.2. Chemical safety assessment**

No

**SECTION 16: Other information**

**Full text of H-phrases as mentioned in section 3**

H225 - Highly flammable liquid and vapour.

H302 - Harmful if swallowed.

H319 - Causes serious eye irritation.

H336 - May cause drowsiness or dizziness.

H373 - May cause damage to organs through prolonged or repeated exposure<sup>a</sup>.

EUH066 - Repeated exposure may cause skin dryness or cracking.

**The full text of identified uses as mentioned in section 1**

-

**Additional label elements**

Not applicable

**Other**

In accordance with Regulation (EC) No. 1272/2008 (CLP) the evaluation of the classification of the mixture is based on:

The classification of the mixture in regard of physical hazards has been based on experimental data.

The classification of the mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP)

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

**The safety data sheet is validated by**

Cecilia Evaldsson

**Date of last essential change**

**(First cipher in SDS version)**

-

**Date of last minor change**

**(Last cipher in SDS version)**

-