

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

Tectyl Remover Strong

Product no.

-

REACH registration number

Not applicable

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Graffiti Removal

Uses advised against

-

The full text of any mentioned and identified use categories are given in section 16

1.3. Details of the supplier of the safety data sheet

Company and address

Blue & Green AB
Stenorsvägen 52
261 44 Landskrona
Sweden
Tfn: +46 418 399000
Fax: +46 418 13199
www.blueandgreen.se

E-mail

info@blueandgreen.se

SDS date

2020-09-22

SDS Version

1.0

1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service). See section 4 "First aid measures".

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Asp. Tox. 1; H304
Skin Sens. 1; H317
Eye Irrit. 2; H319
STOT RE 1; H372
Aquatic Chronic 3; H412
See full text of H-phrases in section 2.2.

2.2. Label elements

Hazard pictogram(s)**Signal word**

Danger

Hazard statement(s)

May be fatal if swallowed and enters airways. (H304)

According to EC-Regulation 2015/830

May cause an allergic skin reaction. (H317)
 Causes serious eye irritation. (H319)
 Causes damage to organs through prolonged or repeated exposure. (H372)
 Harmful to aquatic life with long lasting effects. (H412)

Precautionary statements

General If medical advice is needed, have product container or label at hand. (P101).
 Keep out of reach of children. (P102).
Prevention Do not breathe mist/vapours/fume/spray. (P260).
Response Get medical advice/attention if you feel unwell. (P314).
Storage Store locked up. (P405).
Disposal Dispose of contents/container to an approved waste disposal plant. (P501).

Identity of the substances primarily responsible for the major health hazards

naphtha (råolie), hydroafsvovlet tung; Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics; Amides, C12-18, and, C18-unsatd, N-, hydroxyethyl, ethoxylated

Additional labelling

Not applicable

Unique formula identifier (UFI)

DTFT-CYKX-J00J-24KU

2.3. Other hazards

This product contains substances that can cause chemical pneumonia if inhaled. The symptoms of chemical pneumonia may appear after several hours.

Additional warnings

Tactile warning. If this product is sold in retail, it must be delivered with child-resistant fastening.

VOC (volatile organic compound)

Not applicable

SECTION 3: Composition/information on ingredients

3.1/3.2. Substances/Mixtures

NAME: naphtha (råolie), hydroafsvovlet tung
 IDENTIFICATION NOS.: CAS-no: 64742-82-1 EC-no: 265-185-4 REACH-no: 01-2119473977-17
 CONTENT: 40-60%
 CLP CLASSIFICATION: Asp.Tox 1; STOT RE1; Aquatic Chronic 3; H304, H372, H412, EUH066

NAME: Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics
 IDENTIFICATION NOS.: EC-no: 918-481-9 REACH-no: 01-2119457273-39
 CONTENT: 25-40%
 CLP CLASSIFICATION: Asp.Tox.1; H304
 NOTE: O

NAME: 2-ethylhexyl laurate
 IDENTIFICATION NOS.: CAS-no: 20292-08-4 EC-no: 243-697-9 REACH-no: 01-2119970548-24
 CONTENT: 15 - <25%
 CLP CLASSIFICATION: NA

NAME: Amides, C12-18, and, C18-unsatd, N-, hydroxyethyl, ethoxylated
 IDENTIFICATION NOS.: CAS-no: 157707-44-3 EC-no: 500-350-9
 CONTENT: 2.5 - <5%
 CLP CLASSIFICATION: Skin Irrit. 2, Skin Sens. 1, Eye Dam. 1
 H315, H317, H318

NAME: (2-methoxymethylethoxy)propanol
 IDENTIFICATION NOS.: CAS-no: 34590-94-8 EC-no: 252-104-2 REACH-no: 01-2119450011-60
 CONTENT: 1 - <2.5%
 CLP CLASSIFICATION:
 NOTE: O L

(*) O = Organic solvent L = European occupational exposure limit. See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

Eye Cat. 2 Sum = Sum(Ci/S(G)CLi) = 2 - 3
 Skin Cat. 2 Sum = Sum(Ci/S(G)CLi) = 0.2 - 0.3
 N chronic (CAT 3) Sum = Sum(Ci/(M(chronic)ⁱ*25)^{0.1}*10[^]CATi) = 1.6 - 2.4

According to EC-Regulation 2015/830

Detergent:
> 30%: AROMATIC HYDROCARBONS
15 - 30%: ALIPHATIC HYDROCARBONS
< 5%: NON-IONIC SURFACTANTS

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. The doctor can contact The National Poisons Information Service: Dial 0344 892 0111 (24 h service). Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Bring the person into fresh air and stay with him/her.

Skin contact

Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with soap and water.

Eye contact

Remove contact lenses. Flush eyes immediately with plenty of water or isotonic water (20-30°C) for at least 5 minutes and continue until irritation stops. Make sure to flush under the upper and lower eyelids. If irritation continues, contact a doctor. Continue flushing during transport.

Ingestion

Do not induce vomiting! If vomiting occurs, keep head facing down to prevent vomit entering the lungs. Call a doctor or ambulance. Symptoms of chemical pneumonia can appear after several hours. People who have swallowed the product should be kept under medical attention for a minimum of 48 hours.

Burns

Not applicable

4.2. Most important symptoms and effects, both acute and delayed

This product contains substances that can cause chemical pneumonia if inhaled. The symptoms of chemical pneumonia may appear after several hours.

Sensitisation: This product contains substances, which may trigger allergic reaction upon dermal contact. Manifestation of allergic reactions typically takes place within 12-72 hours after exposure.

This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Call a POISON CENTER/doctor if you feel unwell.

Information to medics

Bring this safety data sheet.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Recommended: alcohol-resistant foam, carbonic acid, powder, water mist.

5.2. Special hazards arising from the substance or mixture

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous catabolic substances are produced. These are: Carbon oxides. Fire will result in dense black smoke. Exposure to combustion products may harm your health. Fire fighters should wear appropriate protection equipment. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid direct contact with spilled substances. Avoid inhalation of vapours from spilled material.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities. It is recommended to install waste collection trays to prevent emissions to the

According to EC-Regulation 2015/830

waste water system and surrounding environment.

6.3. Methods and material for containment and cleaning up

Use sand, sawdust, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations.

6.4. Reference to other sections

See section on "Disposal considerations" in regard of handling of waste. See section on 'Exposure controls/personal protection' for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Smoking, storage of tobacco, consumption and storage of food or liquids are not allowed in the workrooms. It is recommended to install waste collection trays to prevent emissions to the waste water system and surrounding environment. See section on 'Exposure controls/personal protection' for information on personal protection. Avoid direct contact with the product.

7.2. Conditions for safe storage, including any incompatibilities

Always store in containers of the same material as the original container. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Storage temperature

Room temperature 18 to 23°C

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

OEL

(2-methoxymethylethoxy)propanol

Long-term exposure limit (8-hour TWA reference period): 50 ppm | 308 mg/m³

Short-term exposure limit (15-minute reference period): - ppm | - mg/m³

Comments: Sk (Sk = Can be absorbed through skin.)

DNEL / PNEC

DNEL ((2-methoxymethylethoxy)propanol): 283 mg/kg bw/day

Exposure: Dermal

Duration of Exposure: Long term – Systemic effects - Workers

DNEL ((2-methoxymethylethoxy)propanol): 308 mg/kg

Exposure: Inhalation

Duration of Exposure: Long term – Systemic effects - Workers

DNEL ((2-methoxymethylethoxy)propanol): 121 mg/kg bw/day

Exposure: Dermal

Duration of Exposure: Long term – Systemic effects - General population

DNEL ((2-methoxymethylethoxy)propanol): 37.2 mg/m³

Exposure: Inhalation

Duration of Exposure: Long term – Systemic effects - General population

DNEL ((2-methoxymethylethoxy)propanol): 36 mg/kg bw/day

Exposure: Oral

Duration of Exposure: Long term – Systemic effects - General population

DNEL (naphtha (råolie), hydroafsvovlet tung): 330mg/m³

Exposure: Inhalation

Duration of Exposure: Long term – Systemic effects - Workers

DNEL (naphtha (råolie), hydroafsvovlet tung): 44mg/kg/day

Exposure: Dermal

Duration of Exposure: Long term – Systemic effects - Workers

DNEL (naphtha (råolie), hydroafsvovlet tung): 71mg/m³

Exposure: Inhalation

Duration of Exposure: Long term – Systemic effects - General population

DNEL (naphtha (råolie), hydroafsvovlet tung): 26mg/kg/day

Exposure: Dermal

Duration of Exposure: Long term – Systemic effects - General population

According to EC-Regulation 2015/830

DNEL (naphtha (råolie), hydroafsvovlet tung): 26mg/kg/day
 Exposure: Oral
 Duration of Exposure: Long term – Systemic effects - General population

PNEC ((2-methoxymethylethoxy)propanol): 19 mg/l
 Exposure: Freshwater

PNEC ((2-methoxymethylethoxy)propanol): 1.9 mg/l
 Exposure: Marine water

PNEC ((2-methoxymethylethoxy)propanol): 190 mg/l
 Exposure: Intermittent release

PNEC ((2-methoxymethylethoxy)propanol): 70.2 mg/kg/dwt
 Exposure: Freshwater sediment

PNEC ((2-methoxymethylethoxy)propanol): 7.02 mg/kg/dwt
 Exposure: Marine water sediment

PNEC ((2-methoxymethylethoxy)propanol): 2.74 mg/kg
 Exposure: Soil

PNEC ((2-methoxymethylethoxy)propanol): 4168 mg/l
 Exposure: Sewage Treatment Plant

8.2. Exposure controls

Compliance with the accepted occupational exposure limits values should be controlled on a regular basis.

General recommendations

Observe general occupational hygiene standards.

Exposure scenarios

There is no appendix to this safety data sheet.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

Ensure emergency eyewash and -showers are clearly marked.

Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

Measures to avoid environmental exposure

Keep containment materials near the workplace. If possible, collect spillage during work.

Individual protection measures, such as personal protective equipment



Generally

Use only CE marked protective equipment.

Respiratory Equipment

Recommended: A. Class 1 (low capacity). Brown

Skin protection

Dedicated work clothing should be worn. Wear a protective suit in the event of prolonged periods of work with the product.

Hand protection

4H/Barrier

Breakthrough time: > 480 minutes (Class 6)

Eye protection

Wear safety glasses with side shields.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Form

Liquid

According to EC-Regulation 2015/830

Colour	Colourless
Odour	Characteristic
Odour threshold (ppm)	No data available.
pH	No data available.
Viscosity (40°C)	No data available.
Density (g/cm ³)	0.82
Phase changes	
Melting point (°C)	No data available.
Boiling point (°C)	No data available.
Vapour pressure	No data available.
Decomposition temperature (°C)	No data available.
Evaporation rate (n-butylacetate = 100)	No data available.
Data on fire and explosion hazards	
Flash point (°C)	70
Ignition (°C)	No data available.
Auto flammability (°C)	No data available.
Explosion limits (% v/v)	No data available.
Explosive properties	No data available.
Solubility	
Solubility in water	Insoluble
n-octanol/water coefficient	No data available.
9.2. Other information	
Solubility in fat (g/L)	No data available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available

10.2. Chemical stability

The product is stable under the conditions, noted in the section "Handling and storage".

10.3. Possibility of hazardous reactions

Nothing special

10.4. Conditions to avoid

Nothing special

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Substance: (2-methoxymethylethoxy)propanol

Species: Rat

Test: LD50

Route of exposure: Oral

Result: 5000 mg/kg

Substance: (2-methoxymethylethoxy)propanol

Species: Rabbit

Test: LD50

Route of exposure: Dermal

Result: 9510 mg/kg

Substance: (2-methoxymethylethoxy)propanol

Species: Rat

Test: LC50

Route of exposure: Inhalation

Result: 3.35 mg/l 7h ąnga

Substance: Amides,C12-18,and,C18-unsatd,N-,hydroxyethyl,ethoxylated

Species: Rat

Test: LD50

According to EC-Regulation 2015/830

Route of exposure: Oral
Result: >2000 mg/kg

Substance: Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics
Species: Rat
Test: LD50
Route of exposure: Oral
Result: >5000mg/kg

Substance: Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics
Species: Rabbit
Test: LD50
Route of exposure: Dermal
Result: >5000 mg/kg

Substance: Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics
Species: Rat
Test: LC50
Route of exposure: Inhalation
Result: 4951 mg/m³, 4h

Substance: naphtha (råolie), hydroafsvovlet tung
Species: Rat
Test: LD50
Route of exposure: Oral
Result: >15000mg/kg

Substance: naphtha (råolie), hydroafsvovlet tung
Species: Rat
Test: LC50
Route of exposure: Inhalation
Result: >13,1mg/l 4h

Substance: naphtha (råolie), hydroafsvovlet tung
Species: Rat
Test: LD50
Route of exposure: Dermal
Result: >3400mg/kg/bw

Skin corrosion/irritation

Data on substance: Amides,C12-18,and,C18-unsatd,N-,hydroxyethyl,ethoxylated
Test: OECD Guideline 404
Organism: Rabbit
Result: Irritant

Serious eye damage/irritation

Causes serious eye irritation.

Data on substance: Amides,C12-18,and,C18-unsatd,N-,hydroxyethyl,ethoxylated
Test: OECD Guideline 405
Organism: Rabbit
Result: Risk for serious eye damage

Respiratory or skin sensitisation

May cause an allergic skin reaction. Data on substance: Amides,C12-18,and,C18-unsatd,N-,hydroxyethyl,ethoxylated
Result: Can cause an allergic reaction

Germ cell mutagenicity

No data available.

Carcinogenicity

No data available.

Reproductive toxicity

No data available.

STOT-single exposure

No data available.

STOT-repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard

May be fatal if swallowed and enters airways.

Long term effects

This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

SECTION 12: Ecological information

12.1. Toxicity

Substance: (2-methoxymethylethoxy)propanol
Species: Fish

According to EC-Regulation 2015/830

Test: LC50
Duration: 96h
Result: >1000 mg/l

Substance: (2-methoxymethylethoxy)propanol
Species: Daphnia
Test: EC50
Duration: 48h
Result: 1919 mg/l

Substance: (2-methoxymethylethoxy)propanol
Species: Daphnia
Test: NOEC
Duration: 22d
Result: 0.5 mg/l

Substance: (2-methoxymethylethoxy)propanol
Species: Algae
Test: EC50
Duration: 72h
Result: 969 mg/l

Substance: Amides,C12-18,and,C18-unsatd,N-,hydroxyethyl,ethoxylated
Species: Fish
Test: LC50
Duration: 96h
Result: >1-10 mg/l

Substance: Amides,C12-18,and,C18-unsatd,N-,hydroxyethyl,ethoxylated
Species: Daphnia
Test: EC50
Duration: 48h
Result: >1-10 mg/l

Substance: Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics
Species: Fish
Test: LC50
Duration: 96h
Result: >1000mg/l

Substance: Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics
Species: Algae
Test: EC50
Duration: 72h
Result: >1000mg/l

Substance: Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics
Species: Daphnia
Test: EC50
Duration: 48h
Result: >1000mg/l

Substance: naphtha (råolie), hydroafsvovlet tung
Species: Fish
Test: LC50
Duration: 96h
Result: 10-100mg/l

Substance: naphtha (råolie), hydroafsvovlet tung
Species: Algae
Test: EC50
Duration: 72h
Result: 10-100mg/l

Substance: naphtha (råolie), hydroafsvovlet tung
Species: Daphnia
Test: EC50
Duration: 48h
Result: 100-200mg/l

12.2. Persistence and degradability

Substance	Biodegradability	Test	Result
(2-methoxymethylethoxy)propano...	Yes	DOC Die-Away Test	75%
Amides,C12-18,and,C18-unsatd,N...	Yes	CO2 Evolution Test	>60%

According to EC-Regulation 2015/830

Hydrocarbons, C10-C13, n-alkan... naphtha (råolie), hydroafsvovl...	Yes Yes	CO2 Evolution Test Manometric Respirometry Test	80 74,7
12.3. Bioaccumulative potential			
Substance (2-methoxymethylethoxy)propano... Amides, C12-18, and, C18-unsatd, N... naphtha (råolie), hydroafsvovl...	Potential bioaccumulation No No Yes	LogPow 0.006 No data available No data available	BCF No data available No data available No data available
12.4. Mobility in soil (2-methoxymethylethoxy)propano...: Log Koc= 0.28 (High mobility potential).			
12.5. Results of PBT and vPvB assessment This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.			
12.6. Other adverse effects This product contains substances, which may cause adverse long-term effects to the aquatic environment. This product contains substances with the potential of bioaccumulation resulting in the risk of accumulation in the food chain. Bioaccumulative substances are concentrated in adipose tissue and are not easily secreted.			

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product is covered by the regulations on hazardous waste.

Waste

EWC code

-

Specific labelling

Not applicable

Contaminated packing

Contaminated packaging must be disposed of similarly to the product.

SECTION 14: Transport information

14.1 – 14.4

Not dangerous goods according to ADR, IATA and IMDG.

ADR/RID

14.1. UN number -
14.2. UN proper shipping name -
14.3. Transport hazard
class(es) -
14.4. Packing group -
Notes -
Tunnel restriction code -

IMDG

UN-no. -
Proper Shipping Name -
Class -
PG* -
EmS -
MP** -
Hazardous constituent -

IATA/ICAO

UN-no. -
Proper Shipping Name -
Class -
PG* -

14.5. Environmental hazards

-

14.6. Special precautions for user

-

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available

(*) Packing group

(**) Marine pollutant

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

According to EC-Regulation 2015/830

Restrictions for application

People under the age of 18 shall not be exposed to this product cf. Council Directive 94/33/EC of 22 June 1994 on the protection of young people at work.

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

Demands for specific education

-

Additional information

The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

Seveso

-

Biocidal reg. no.

Not applicable

Sources

Council Directive 92/85/EEC on the introduction of measures to encourage improvements in the safety and health at work of pregnant workers and workers who have recently given birth or are breastfeeding.

Council Directive 94/33/EC of 22 June 1994 on the protection of young people at work.

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677. The Stationery Office, 2002.

Regulation (EC) No 648/2004 of the European Parliament and of the Council of 31 March 2004 on detergents.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (CLP).

Regulation (EC) 1907/2006 (REACH).

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

H304 - May be fatal if swallowed and enters airways.

H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction.

H318 - Causes serious eye damage.

H372 - Causes damage to organs through prolonged or repeated exposure.

H412 - Harmful to aquatic life with long lasting effects.

EUH066 - Repeated exposure may cause skin dryness or cracking.

The full text of identified uses as mentioned in section 1

-

Additional label elements

Not applicable

Other

In accordance with Regulation (EC) No. 1272/2008 (CLP) the evaluation of the classification of the mixture is based on:

The classification of the mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP)

The classification of the mixture in regard of environmental hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP)

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The safety data sheet is validated by



According to EC-Regulation 2015/830

David Löwenstein

**Date of last essential change
(First cipher in SDS version)**

-

**Date of last minor change
(Last cipher in SDS version)**

-

ALPHAOMEGA. Licens nr.:3830228684, Blue & Green AB, 7.0.1.11
www.chymeia.com